



Perma Tile Grout



**Founded, Based and
MADE IN THE U.S.A.**

Non Yellowing
Fade Resistant Tile Grout

DESCRIPTION:

PERMA TILE GROUT is a special blend of Portland cements, fortifiers and graded fillers.

PERMA TILE GROUT is suitable for all grouting applications in the areas of floor and wall tile, shower stalls, towel rack and soap dishes, sink tops and mosaic tile applications.

ADVANTAGES:

- Mix with water only
- Produces a strong and durable grout joint
- Remains chip, shrink, stain and water resistant
- Bright white, non-yellowing and fade resistant
- May be tinted to match tile

SPECIAL NOTES:

1. **PERMA TILE GROUT** should be cured by misting with water at least once in the first 24 hours.
2. Suitable for new or restoration work

SURFACE PREPARATION:

For new installations allow the tile to set for 18 to 24 hours prior to proceeding with grouting. Tile and grout joints should be clean and free from any dust or adhesive. For re-grouting of old joints you must remove all dead or unsound grout with a grout joint saw. Wipe the surface with a damp cloth to remove any dust or dried soap from the tile and joint areas. No priming is required.

MIXING:

Add clean water to a mixing pail and gradually add the **PERMA TILE GROUT** to the pail while mixing. Continue to mix and add grout until a soft paste consistency is achieved. Let stand for 15 minutes and then re-temper. A small amount of additional water may be needed.

APPLICATION:

Apply **PERMA TILE GROUT** with a rubber grout float held at a 30° angle. Work grout into the joints with strokes at 45° angle to the grout joints.

Work in material until all gaps and air pockets have been removed. Remove excess material with grout float and move onto an adjoining area. Work in small areas that can be completed in 15 to 20 minutes.

CLEANING:

Allow the **PERMA TILE GROUT** to firm up but do not allow to dry before sponging. To remove excess material use a damp sponge in a circular motion. Do not use excessive water. Keep sponge clean by frequently rinsing in a bucket of water.

Do not allow **PERMA TILE GROUT** to dry prior to cleaning with a damp sponge.

After 2 to 3 hours a white haze will form on the tiles. This haze can be removed with a nylon sponge and then the tiles can be polished with a clean cloth.

03 61 00
Cement Grouting

3

03 50 00
Concrete Repair

3

PACKAGING:

5 lb. Tubs 8/Case
3000 lb. Super Sacks

COLOR:

White

WATER RATIO :

8.5QTS TO 50LBS

SHELF LIFE:

1 year when stored in original unopened container.

APPROXIMATE COVERAGE:

1 lb. of Tile Grout will cover 12 to 16 ft²

WEIGHT:

110 lbs. per cubic foot

APPLICATION TEMPERATURE

RANGE:

35° - 95°F

PERMA TILE GROUT

PRECAUTIONS:

Dispose of waste materials in accordance with Federal, State and local regulations

The use of a dust mask, safety goggles and rubber gloves are recommended.

Caution: Contains Portland Cement which is highly caustic

In case of contact, flush eyes with water. Wash skin with soap and water. Consult a physician

STORAGE:

Store between 50°F (10°C) and 95°F (35°C) in a dry area.

Keep tightly sealed when not in use and store out of direct sunlight.

Avoid high humidity.

FLAMMABILITY: (ASTM E-84)

Flame Spread: -0-

Fuel Contribution: -0-

Smoke Development: -0-

VOLITALE ORGANIC COMPOUNDS

0 g/l

CLEAN UP:

Clean tools with water immediately after use or by mechanical means once dry.

Dispose of waste materials in accordance with Federal, State and local regulations.

HEALTH AND SAFETY:

Always refer to the Safety Data Sheet (SDS) prior to using this product for full Health, Safety and Handling guidelines. SDS sheets are available by calling 215.638.4400 or you can visit www.cgmbuildingproducts.com

For Professional Use Only

KEEP OUT OF REACH OF CHILDREN



***Founded, Based and
MADE IN THE U.S.A.***